

COMPANY NAME, INC.
PART # 13579 REV. O
PART DESCRIPTION

REPORT # 44444
FEBRUARY 22, 2011

| ITEM | DIMENSION | TOL. | ZONE | ACTUAL | DEV. | REMARKS |
|------|-------------------------------|------------|--------|------------------|------|---------------------------|
| 1 | DRAFT 2° | ± 0.5° | NOTE 1 | COMPLIES | | |
| 2 | .094 WALL THICKNESS | ± .010 | NOTE 3 | 0.0982 0.0979 | | |
| 3 | CORE DFT. 0.5° | ± 0.5° | NOTE 7 | COMPLIES | | |
| 4 | EJ. PADS Ø 1/4 (.2500) | MAX | NOTE 9 | COMPLIES | | |
| 5 | EJ. PADS 1/16 (.0625) HIGH | MAX | NOTE 9 | COMPLIES | | |
| 6 | 3 1/2 (3.5000) | + .0313/-0 | | 3.5080 TYP. | | |
| 7 | 1 3/4 (1.7500) | ± .0313 | | 1.7491 | | |
| 8 | .625 | ± .010 | | 0.6305 0.6209 | | 2 PLACES. |
| 9 | 15/16 (.9375) | ± .0313 | | 0.9349 | | |
| 10 | 7/16 (.4375) | ± .0313 | | 0.4402 | | |
| 11 | .312 | ± .010 | | 0.3113 0.3044 | | 4 PLACES. |
| 12 | R .375 TYP. | ± .010 | | 0.3750 TYP. | | 2 PLACES. |
| 13 | R 1/4 (.2500) TYP. | ± .0313 | | 0.2500 TYP. | | MEAS @ + DRAFT, 2 PLACES. |
| 14 | R .375 TYP. | ± .010 | | 0.3750 TYP. | | 4 PLACES. |
| 15 | .235 | ± .010 | | 0.2417 0.2344 | | 4 PLACES. |



AS 9100 Rev. B ISO 9001:2008

COMPANY NAME, INC.
PART # 13579 REV. O
PART DESCRIPTION

REPORT # 44444
FEBRUARY 22, 2011

| ITEM | DIMENSION | TOL. | ZONE | ACTUAL | DEV. | REMARKS |
|------|---------------------|------------|------|------------------|------|----------------------|
| 16 | 1 3/4 (1.7500) | ± .0313 | | 1.7451 | | |
| 17 | 1.875 | ± .010 | | 1.8850 1.8825 | | |
| 18 | 1.500 | ± .010 | | 1.5055 1.4978 | | |
| 19 | 3 1/2 (3.5000) | + .0313/-0 | | 3.5080 | | |
| 20 | .750 | ± .010 | | 0.7527 0.7489 | | |
| 21 | 2.312 | ± .010 | | 2.3149 | | |
| 22 | .235 | ± .010 | | 0.2417 0.2344 | | |
| 23 | 1 1/2 (1.5000) | ± .0313 | | 1.5055 1.4875 | | 2 PLACES. |
| 24 | 45° TYP. | ± 0.5° | | 44.60° | | |
| 25 | R 1/32 (.0313) TYP. | ± .0313 | | 0.0313 TYP. | | 4 PLACES. |
| 26 | R 3/4 (.7500) TYP. | ± .0313 | | 0.7500 TYP. | | 2 PLACES. |
| 27 | 1 1/8 (1.1250) | ± .0313 | | 1.1275 | | MEASURED AT + DRAFT. |
| 28 | 2 3/4 (2.7500) | ± .0313 | | 2.7502 | | |
| 29 | 9/16 (.5625) | ± .0313 | | 0.5646 | | |
| 30 | 2 1/16 (2.0625) | ± .0313 | | 2.0675 | | |
| 31 | 1 9/16 (1.5625) | ± .0313 | | 1.5683 | | |



AS 9100 Rev. B ISO 9001:2008

COMPANY NAME, INC.
PART # 13579 REV. O
PART DESCRIPTION

REPORT # 44444
FEBRUARY 22, 2011

| ITEM | DIMENSION | TOL. | ZONE | ACTUAL | DEV. | REMARKS |
|------|----------------------|---------|----------|------------------|------|----------------------|
| 32 | R 5/32 (.1563) TYP. | ± .0313 | | 0.1563 TYP. | | 4 PLACES. |
| 33 | 1/8 (.1250) TYP. | ± .0313 | | 0.1231 0.1225 | | |
| 34 | R 5/16 (.3125) TYP. | ± .0313 | | 0.3009 | | |
| 35 | R 5/32 (.1563) TYP. | ± .0313 | | 0.1563 TYP. | | 4 PLACES |
| 36 | 3/16 (.1875) TYP. | ± .0313 | | 0.1732 | | |
| 37 | SR 3/16 (.1875) TYP. | ± .0313 | SEC. B-B | 0.1875 TYP. | | 2 PLACES. |
| 38 | R 1/16 (.0625) TYP. | ± .0313 | SEC. B-B | 0.0625 TYP. | | |
| 39 | 1/8 (.1250) | ± .0313 | SEC. B-B | NOT INSP. | | DWG. INTENT UNCLEAR. |
| 40 | 3/32 (.0938) | ± .0313 | SEC. B-B | NOT INSP. | | DWG. INTENT UNCLEAR. |
| 41 | R 1/32 (.0313) TYP. | ± .0313 | SEC. B-B | 0.0313 TYP. | | 2 PLACES. |
| 42 | Ø 3/8 (.3750) TYP. | ± .0313 | | 0.3647 | | |
| 43 | R 11/64 (.1719) TYP. | ± .0313 | | 0.1719 TYP. | | 4 PLACES. |
| 44 | 1/8 (.1250) | ± .0313 | | 0.1241 | | |
| 45 | 2.625 | ± .010 | | 2.6292 2.6286 | | |
| 46 | 1.312 | ± .005 | | 1.3157 1.3110 | | |
| 47 | R 7/16 (.4375) TYP. | ± .0313 | | 0.4375 TYP. | | 4 PLACES. |
| 48 | R 1/16 (.0625) TYP. | ± .0313 | | 0.0625 0.0313 | | 5 PLACES. |