

COMPANY NAME, INC.
PART # 13579 REV. O
PART DESCRIPTION

REPORT # 44444
FEBRUARY 22, 2011

ITEM	DIMENSION	TOL.	ZONE	ACTUAL	DEV.	REMARKS
1	DRAFT 2°	± 0.5°	NOTE 1	COMPLIES		
2	.094 WALL THICKNESS	± .010	NOTE 3	0.0982 0.0979		
3	CORE DFT. 0.5°	± 0.5°	NOTE 7	COMPLIES		
4	EJ. PADS Ø 1/4 (.2500)	MAX	NOTE 9	COMPLIES		
5	EJ. PADS 1/16 (.0625) HIGH	MAX	NOTE 9	COMPLIES		
6	3 1/2 (3.5000)	+ .0313/-0		3.5080 TYP.		
7	1 3/4 (1.7500)	± .0313		1.7491		
8	.625	± .010		0.6305 0.6209		2 PLACES.
9	15/16 (.9375)	± .0313		0.9349		
10	7/16 (.4375)	± .0313		0.4402		
11	.312	± .010		0.3113 0.3044		4 PLACES.
12	R .375 TYP.	± .010		0.3750 TYP.		2 PLACES.
13	R 1/4 (.2500) TYP.	± .0313		0.2500 TYP.		MEAS @ + DRAFT, 2 PLACES.
14	R .375 TYP.	± .010		0.3750 TYP.		4 PLACES.
15	.235	± .010		0.2417 0.2344		4 PLACES.



AS 9100 Rev. B ISO 9001:2008

COMPANY NAME, INC.
PART # 13579 REV. O
PART DESCRIPTION

REPORT # 44444
FEBRUARY 22, 2011

ITEM	DIMENSION	TOL.	ZONE	ACTUAL	DEV.	REMARKS
16	1 3/4 (1.7500)	± .0313		1.7451		
17	1.875	± .010		1.8850 1.8825		
18	1.500	± .010		1.5055 1.4978		
19	3 1/2 (3.5000)	+ .0313/-0		3.5080		
20	.750	± .010		0.7527 0.7489		
21	2.312	± .010		2.3149		
22	.235	± .010		0.2417 0.2344		
23	1 1/2 (1.5000)	± .0313		1.5055 1.4875		2 PLACES.
24	45° TYP.	± 0.5°		44.60°		
25	R 1/32 (.0313) TYP.	± .0313		0.0313 TYP.		4 PLACES.
26	R 3/4 (.7500) TYP.	± .0313		0.7500 TYP.		2 PLACES.
27	1 1/8 (1.1250)	± .0313		1.1275		MEASURED AT + DRAFT.
28	2 3/4 (2.7500)	± .0313		2.7502		
29	9/16 (.5625)	± .0313		0.5646		
30	2 1/16 (2.0625)	± .0313		2.0675		
31	1 9/16 (1.5625)	± .0313		1.5683		



AS 9100 Rev. B ISO 9001:2008

COMPANY NAME, INC.
PART # 13579 REV. O
PART DESCRIPTION

REPORT # 44444
FEBRUARY 22, 2011

ITEM	DIMENSION	TOL.	ZONE	ACTUAL	DEV.	REMARKS
32	R 5/32 (.1563) TYP.	± .0313		0.1563 TYP.		4 PLACES.
33	1/8 (.1250) TYP.	± .0313		0.1231 0.1225		
34	R 5/16 (.3125) TYP.	± .0313		0.3009		
35	R 5/32 (.1563) TYP.	± .0313		0.1563 TYP.		4 PLACES
36	3/16 (.1875) TYP.	± .0313		0.1732		
37	SR 3/16 (.1875) TYP.	± .0313	SEC. B-B	0.1875 TYP.		2 PLACES.
38	R 1/16 (.0625) TYP.	± .0313	SEC. B-B	0.0625 TYP.		
39	1/8 (.1250)	± .0313	SEC. B-B	NOT INSP.		DWG. INTENT UNCLEAR.
40	3/32 (.0938)	± .0313	SEC. B-B	NOT INSP.		DWG. INTENT UNCLEAR.
41	R 1/32 (.0313) TYP.	± .0313	SEC. B-B	0.0313 TYP.		2 PLACES.
42	Ø 3/8 (.3750) TYP.	± .0313		0.3647		
43	R 11/64 (.1719) TYP.	± .0313		0.1719 TYP.		4 PLACES.
44	1/8 (.1250)	± .0313		0.1241		
45	2.625	± .010		2.6292 2.6286		
46	1.312	± .005		1.3157 1.3110		
47	R 7/16 (.4375) TYP.	± .0313		0.4375 TYP.		4 PLACES.
48	R 1/16 (.0625) TYP.	± .0313		0.0625 0.0313		5 PLACES.